

# NoTouch® Stainless Steel Button



## PRODUCT OVERVIEW

This touch free button applies NoTouch® technology which helps eliminate the spread of germs in any public building. To exit, a person must simply wave their hand in front of the device. The infrared will detect the motion and unlatch the time adjustable door.

NoTouch® Stainless Steel Button offers three standard models: OPEN, EXIT and the international exit symbol representing a person exiting. Custom models are also available with printing capabilities at STI's corporate and international offices.

The button is constructed of corrosion resistant stainless steel, allowing it to take tough knocks in stride. This durable and long lasting button is easily installed within minutes right on site. The faceplate is slightly oversized for retrofit applications to cover marks from a previous install.

## HOW IT WORKS

Buttons are shipped with the red light indicating standby, and it changes to green when active. Wave a hand in front of the red illuminated button and the colour turns to green indicating the door released. Option for the opposite colours, green/standby and red/active, can be easily changed on site.

## KEY FEATURES

### General Information

- Ideal for public buildings of almost any kind.
- Helps reduce the spread of germs.
- State indicator LED – Standby/ Active Red/Green (default) or selectable green/red.
- Switch IP65.
- One year guarantee on electro mechanical and electronic components.

### Construction

- Faceplate is constructed of medical/food grade 304 stainless steel.
- Button constructed of polycarbonate.
- Heavy duty switch plate and backbox 1.5mm thick.

### Installation

- Faceplate is slightly oversized to cover old installation marks.
- Operating temperature 14°F to 158°F (-10°C to 70°C).
- Operating life:
  - Mechanical relay 1,000,000 cycles
  - IR sensor 100,000 hours

### Electronics

- NoTouch® infrared detection.
- Operating voltage 12VDC – 24VDC, 45mA (max.), Slim model 35mA (max.)
- Detection range 1.5~6in, 4cm~15cm (±25%).
- Form "C" dry contact, 0.5A @120VAC, 1A @ 24VDC.
- Adjustable relay latch 0.5~20 sec.

### Options

- Available sizes.
- Slim/Mullion mount, back box included.
- US single gang, back box available.
- US double gang.
- European single gang, back box available.
- Language and custom labels

# NoTouch® Stainless Steel Button

Dimensions and Technical Information

## MODELS AVAILABLE

Slim/mullion (includes back box)

**NT-SS000-EN** Door symbol (running man)

**NT-SS001-EN** EXIT

**NT-SS002-EN** OPEN

**NTSS00ZA** CUSTOM TEXT

US single gang

**NT-SS100-EN** Door symbol (running man)

**NT-SS101-EN** EXIT

**NT-SS102-EN** OPEN

**NTSS10ZA** CUSTOM TEXT

US double gang

**NT-SS200-EN** Door symbol (running man)

**NT-SS201-EN** EXIT

**NT-SS202-EN** OPEN

**NTSS20ZA** CUSTOM TEXT

European single gang

**NT-SS300-EN** Door symbol (running man)

**NT-SS301-EN** EXIT

**NT-SS302-EN** OPEN

**NTSS30ZA** CUSTOM TEXT

\*Change -EN to -ES for Spanish, -FR for French

Surface Mount Back Box

**KIT-BB0SS** Back box for slim/mullion

**KIT-BB1SS** Back box for US single gang

**KIT-BB3SS** Back box for European single gang

## APPROVALS & WARRANTY

### Testing

It has been tested and approved or listed by:

- CE

- UK CA

### Warranty

One year guarantee on electro mechanical and electronic components.



**Safety Technology  
International**

Taylor House  
34 Sherwood Road  
Bromsgrove  
Worcestershire  
B60 3DR, England

Tel: +44 (0)1527 520 999  
Fax: +44 (0)1527 501 999  
info@sti-emea.com  
www.sti-emea.com

2306 Airport Road  
Waterford, Michigan  
48327, USA

Tel: 248-673-9898  
Fax: 248-673-1246  
info@sti-usa.com  
www.sti-usa.com